Printing date: 22.05.2023 Version: 4 (replaces version 3) Revision: 22.05.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· Product identifier

• Trade name: Royal Gas 250 ml 75-50025-0000

· Article number: 900148

- · Relevant identified uses of the substance or mixture and uses advised against -
- · Application of the substance / the mixture Aid
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Klemko Techniek B.V. Nederland

Nieuwegracht 26 NL-3763 LB Soest

Nederland

Mail: info@klemko.nl Tel: +31 (0) 88 0023300

Monday - Friday: 08:30 - 17:00 uur

SECTION 2: Hazards identification

· Classification of the substance or mixture



Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

- · Label elements
- · GHS label elements

The product is classified and labelled according to the Globally Harmonised System (GHS).

· Hazard pictograms



- · Signal word Danger
- · Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

- Precautionary statements
- P101 If medical advice is needed, have product container or label at hand.
- P102 Keep out of reach of children.
- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P211 Do not spray on an open flame or other ignition source.
- P251 Do not pierce or burn, even after use.
- P261 Avoid breathing mist/vapours/spray.
- P271 Use only outdoors or in a well-ventilated area.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- vPvB: Not applicable.

GB

Printing date: 22.05.2023 Version: 4 (replaces version 3) Revision: 22.05.2023

Trade name: Royal Gas 250 ml

75-50025-0000

(Contd. of page 1)

SECTION 3: Composition/information on ingredients

- · Mixtures
- · Description: Active substance with propellant

· Dangerous components:		
CAS: 106-97-8 EINECS: 203-448-7 Reg.nr.: 01-2119474691-32	butane (containing < 0.1% butadiene (203-450-8), Note K) Flam. Gas 1A, H220; Press. Gas (Comp.), H280	50-<75%
CAS: 74-98-6 EINECS: 200-827-9 Reg.nr.: 01-2119486944-21	propane Flam. Gas 1A, H220; Press. Gas (Comp.), H280	25-<50%
CAS: 75-28-5 EINECS: 200-857-2 Reg.nr.: 01-2119485395-27	isobutane (containing < 0,1 % butadiene (203-450-8), Note K) Flam. Gas 1A, H220; Press. Gas (Comp.), H280	2.5-<10%

· Additional information:

Aerosols and containers fitted with a solid atomizer containing substances or mixtures classified as hazardous by aspiration shall not be labelled for that hazard.

The text of the hazard statements mentioned here can be found in chapter 16.

SECTION 4: First aid measures

- · Description of first aid measures
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: Generally the product does not irritate the skin.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: Do not induce vomiting; call for medical help immediately.
- Most important symptoms and effects, both acute and delayed No further relevant information available.
- Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

Water haze

Fire-extinguishing powder

Carbon dioxide

Alcohol resistant foam

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: Mount respiratory protective device.

SECTION 6: Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

· Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

· Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

(Contd. on page 3)

Printing date: 22.05.2023 Version: 4 (replaces version 3) Revision: 22.05.2023

Trade name: Royal Gas 250 ml 75-50025-0000

(Contd. of page 2)

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

- · Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.
- · Information about fire and explosion protection:

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Store in a cool location.

Observe official regulations on storing packagings with pressurised containers.

· Information about storage in one common storage facility:

Observe official regulations on storing packagings with pressurised containers.

· Further information about storage conditions:

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

· Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· Control parameters

· Ingredients w	ith limit values th	at require monitoring	at the workplace

106-97-8 butane (containing < 0.1% butadiene (203-450-8), Note K)

WEL Short-term value: 1810 mg/m³, 750 ppm Long-term value: 1450 mg/m³, 600 ppm Carc (if more than 0.1% of buta-1.3-diene)

74-98-6 propane

OEL Long-term value: 1800 mg/m³, 1000 ppm
Additioneel ingevuld tbv klant voor Hfdst3 SDS

75-28-5 isobutane (containing < 0,1 % butadiene (203-450-8), Note K)

OEL Long-term value: 2400 mg/m³, 1000 ppm Additioneel ingevuld obv klant voor Hfdst 3 SDS

- · Additional information: The lists valid during the making were used as basis.
- · Exposure controls
- · Appropriate engineering controls No further data; see section 7.
- · Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures:

Wash hands before breaks and at the end of work.

General ventilation

· Respiratory protection:

Use suitable respiratory protective device in case of insufficient ventilation.

Filter A2/P2

· Hand protection

Solvent resistant gloves

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation (Contd. on page 4)

GB ·

Printing date: 22.05.2023 Version: 4 (replaces version 3) Revision: 22.05.2023

Trade name: Royal Gas 250 ml 75-50025-0000

(Contd. of page 3)

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.5 mm

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye/face protection

Safety glasses



Tightly sealed goggles

· Body protection:

Use protective suit. (EN-13034/6)

Full skin covering antistatic, chemical and oil resistant clothing and safety shoes are recommended. (EN1149; EN340&EN ISO 13688; EN13034-6).

· Environmental exposure controls Use a suitable container to prevent environmental contamination.

SECTION 9: Physical and chemical properties

· Information on basic physical and chemical properties

· General Information

· Physical state Aerosol

· Colour: According to product specification

Odour: Characteristic
 Odour threshold: Not determined.
 Melting point/freezing point: Undetermined.

· Boiling point or initial boiling point and boiling

range -44.5 °C • Flammability Not applicable.

Lower and upper explosion limit

 · Lower:
 1.5 Vol %

 · Upper:
 10.9 Vol %

 · Flash point:
 -97 °C

 · Ignition Temperature
 365 °C

• pH Mixture is non-polar/aprotic.

· Viscosity:

Kinematic viscosity Dynamic: Not determined Not determined

·Solubility

• water: Not miscible or difficult to mix.

• Partition coefficient n-octanol/water (log value) Not determined. • Vapour pressure at 20 °C: 8300 hPa

· Density and/or relative density

Density at 20 °C:

• Relative density

• Vapour density

Not determined.

Not determined.

· Other information

· Appearance:

· Form: Aerosol

(Contd. on page 5)

Printing date: 22.05.2023 Version: 4 (replaces version 3) Revision: 22.05.2023

Trade name: Royal Gas 250 ml

75-50025-0000

(Contd. of page 4)

· Important information on protection of health and environment, and on safety.

Ignition temperature: Product is not selfigniting.

· Explosive properties: Product is not explosive. However, formation of

explosive air/vapour mixtures are possible.

· Solvent content:

· Organic solvents: 100.0 % · Solids content: 0.0%

· Change in condition

· Evaporation rate Not applicable.

· Information with regard to physical hazard classes

Void ·Explosives · Flammable gases Void

Extremely flammable aerosol. Pressurised container: · Aerosols

May burst if heated.

Void · Oxidising gases · Gases under pressure Void · Flammable liquids Void · Flammable solids Void · Self-reactive substances and mixtures Void · Pyrophoric liquids Void Pyrophoric solids Void · Self-heating substances and mixtures Void

· Substances and mixtures, which emit flammable

Void gases in contact with water **Oxidising liquids** Void · Oxidising solids Void · Organic peroxides Void · Corrosive to metals Void Desensitised explosives Void

SECTION 10: Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

(Contd. on page 6)

Printing date: 22.05.2023 Version: 4 (replaces version 3) Revision: 22.05.2023

Trade name: Royal Gas 250 ml

75-50025-0000

(Contd. of page 5)

· Information on other hazards

· Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability Not easily biodegradable
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- · Other adverse effects
- · Additional ecological information:
- · General notes: Not hazardous for water.

SECTION 13: Disposal considerations

- · Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information

- · UN number or ID number
- · ADR, ADN, IMDG, IATA UN1950

· UN proper shipping name

· ADR. ADN UN1950 AEROSOLS

· IMDG AEROSOLS

· IATA AEROSOLS, flammable

- · Transport hazard class(es)
- · ADR



· Class 2 5F Gases.

· Label 2.1

(Contd. on page 7)

Printing date: 22.05.2023 Version: 4 (replaces version 3) Revision: 22.05.2023

Trade name: Royal Gas 250 ml 75-50025-0000

	(Contd. of page
· ADN · ADN/R Class:	2 5F
· IMDG, IATA	
· Class	2.1 Gases.
· Label	2.1
· Packing group · ADR, IMDG, IATA	Void
· Environmental hazards:	Not applicable.
· Special precautions for user	Warning: Gases.
· Hazard identification number (Kemler code):	-
· EMS Number:	F-D,S-U
· Stowage Code	SW1 Protected from sources of heat.
	SW2 Clear of living quarters.
· Segregation Code	SG69 For AEROSOLS with a maximum capacity of 1 litre
	Segregation as for class 9. Stow "separated from" class 1 except for division 1.4.
	For AEROSOLS with a capacity above 1 litre:
	Segregation as for the appropriate subdivision of class 2.
	For WASTE AEROSOLS:
	Segregation as for the appropriate subdivision of class 2.
· Maritime transport in bulk according to IMC	
instruments	Not applicable.
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E0
The state of the s	Not permitted as Excepted Quantity
· Transport category	2 D
· Tunnel restriction code	U
· IMDG	47
· Limited quantities (LQ)	1L Code FO
· Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity
	1
· UN "Model Regulation":	UN 1950 AEROSOLS, 2.1

SECTION 15: Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P3a FLAMMABLE AEROSOLS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t

(Contd. on page 8)

Printing date: 22.05.2023 Version: 4 (replaces version 3) Revision: 22.05.2023

Trade name: Royal Gas 250 ml

75-50025-0000

(Contd. of page 7)

· National regulations:

· Breakdown regulations:

Class	Share in %
NK	100.000

- · VOC-CH 100.00 %
- · VOC-EU 556.0 g/l
- · Danish MAL Code 3-1
- · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H220 Extremely flammable gas.

H280 Contains gas under pressure; may explode if heated.

· Classification according to Regulation (EC) No 1272/2008

Physical and chemical properties: The classification is based on the results of the mixtures tested. Health hazards, Environmental hazards: The method of classification of mixtures based on the constituents of the mixture (sum formula).

· Contact: ing. J. Sleumer

· Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

MAL-Code: Måleteknisk Arbejdshygiejnisk Luftbehov (Regulation for the labeling concerning inhalation hazards, Denmark)

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

Flam. Gas 1A: Flammable gases – Category 1A

Aerosol 1: Aerosols – Category 1

Press. Gas (Comp.): Gases under pressure – Compressed gas

* Data compared to the previous version altered. *

GB