

Klemko Techniek B.V.
Phone: +31 (0)880023300
E-mail: info@klemko.nl


klemko®

101580 - SP 4610 R

Geïsoleerde kabelschoenen, PVC

Package type: BX á 100 pce

/productimages/101580.jpg



PRODUCT SPECIFICATIONS:

| | |
|--|--------------------------|
| Bolt dimension (metric) | 10 |
| Flange shape | Ring shape |
| Insulation | Polyvinyl chloride (PVC) |
| Insulated | Yes |
| Colour insulation | Yellow |
| Nominal cross section (mm ²) | 2.63 - 6.64 |
| Polyvinyl chloride (PVC) | |
| Reel/roll packaging | No |
| Sleeve form | Short |
| Colour | Yellow |
| Suitable for solid conductors | No |
| Suitable for stranded conductors | Yes |
| Suitable for fine strand conductors | Yes |
| Suitable for high temperatures (to 650 °C) | No |
| Suitable for insulated varnish | No |
| Suitable for round conductors | Yes |
| Suitable for flat conductors | No |
| Temperature protected till (°C) | 75 |
| For pull protected connections | Yes |
| Material | Copper |
| Surface protection | Tinned |
| Max. current (I _{max}) (A) | 50 |
| Stud size (imperial) | Other |
| Halogen free | No |
| Total length (mm) | 35.5 |
| (mm) | 6.5 |
| (mm) | 15 |
| (mm) | 35.5 |
| Amperage (A) | 48 |
| (V) | 600 |
| Watertight | No |
| Yes | |
| No | |
| No | |