

Klemko Techniek B.V.  
Phone: +31 (0)880023300  
E-mail: info@klemko.nl

# klemko®

## 160210 - KCT-IP68-3P-6-14,5

160210.jpg

Package type: BG á 1 pce

**PRODUCT SPECIFICATIONS:**

For cable outer diameter (mm)	6 - 14.5
Number of inlets	3
Yes	
Contact type	Other
Diameter connector (mm)	31
Type of housing	Variable
Rated current I <sub>n</sub> (A)	24
Ambient temperature (°C)	-20 - +110
Rated voltage (V)	450
Connectable conductor cross section fine-strand without cable end sleeve (mm <sup>2</sup> )	0.2 - 2.5
Connectable conductor cross section fine-strand with cable end sleeve (mm <sup>2</sup> )	0.2 - 2.5
Connectable conductor cross section solid-core (mm <sup>2</sup> )	0.2 - 2.5
Type of electric connection	Spring clamp connection
Material of contact surface	Brass
Housing material	Plastic
Locking mechanism	Gland nut
Inflammability class of insulation material according to with UL94	V0
With protective conductor	No
Degree of protection (IP), mounted	IP68
Number of data contacts	0
Number of power contacts	3
Number of control contacts	0
Material thread ring	Plastic
Screened	No
With status indication	No