

Klemko Techniek B.V.
Phone: +31 (0)880023300
E-mail: info@klemko.nl

klemko®

171050 - A 4630 SR

Geïsoleerde kabelschoenen, Blister

/productimages/171050.jpg

Package type: BME á 25 pce



PRODUCT SPECIFICATIONS:

Insulated	Yes
Polyvinyl chloride (PVC)	
Flange shape	Pin shape
According to DIN	No
Insulation	Polyvinyl chloride (PVC)
Colour insulation	Yellow
Nominal cross section (mm ²)	2.63 - 6.64
Reel/roll packaging	No
Sleeve form	Short
Colour	Yellow
AWG-range	14 - 10
Suitable for solid conductors	No
Suitable for stranded conductors	Yes
Suitable for fine strand conductors	Yes
Suitable for high temperatures (to 650 °C)	No
Suitable for insulated varnish	No
Suitable for round conductors	Yes
Suitable for flat conductors	No
Temperature protected till (°C)	105
For pull protected connections	No
Material	Copper
Surface protection	Tinned
Max. current (I _{max}) (A)	50
Halogen free	No
Flange length (mm)	13
Total length (mm)	25.5
Pin diameter (pin shape terminal) (mm)	2.8
(mm)	13
(mm)	5.6
(mm)	2.8
(mm)	25.5
Amperage (A)	48
(V)	600
Temperature (°C)	75
No	
No	
Packaging	Bag
Watertight	No
No	
No	
No	