

Klemko Techniek B.V.  
Phone: +31 (0)880023300  
E-mail: info@klemko.nl

# klemko®

## 863734 - LCB-SPOT-W-DTW


Led spots, inbouw

863742.jpg

Package type: CT á 1 pce

# PRODUCT SPECIFICATIONS:

Spot	
Mounting method	Built-in
Dimmable	Yes
Colour temperature (K)	2200 - 3000
Colour of light adjustable	Continuously variable
Luminous flux (lm)	0 - 219
Rated luminous flux according to IEC 62722-2-1 (lm)	219
(lm)	0 - 219
(lm/W)	0 - 73
Nominal current (mA)	0 - 500
Nominal voltage (V)	5.6 - 5.6
Voltage type	DC
Max. system power (W)	3
Energy efficiency class of the light source according to EU regulation 2019/2015	G
Beam angle	Wide beam 41-80°
Beam angle (°)	45
Built-in height (mm)	26 - 27
Height/depth (mm)	26
Outer diameter (mm)	50
Built-in diameter (mm)	45 - 48
Housing colour	White
Degree of protection (IP), front side	IP44
Other	
Degree of protection (IP)	IP44
Suitable for ceiling mounting	Yes
Suitable for suspended mounting	No
Luminous flux adjustable	Continuously variable
Suitable for lamp power (W)	3 - 3
Suitable for traverse mounting	No
Suitable for pedestal/floor mounting	No
Suitable for light-track mounting	No
Suitable for clamp-mounting	Yes
Adjustability	Rotating and swivelling
With movement sensor	No
With light sensor	No
Lamp type	LED not exchangeable
With light source	Yes
Electrical connection with connector system	Yes
Type of control gear	LED operating device current-controlled
With control gear	No
Colour of light	White
Housing material	Aluminium



Moulded-on	
Reflector	Other
Light sharing	Symmetric
Colour rendering index CRI	80-89
Suitable for surface mounting	No
Suitable for built-in mounting	Yes
Optics	Reflector
Surface protection	Lacquered
Material cover	Glass transparent
(cm)	100
Light distributor	Diffuser lens/optic/panel
Reflector colour	Silver
Light outlet	Direct
Number of poles	2
Connection type	Other
Colour consistency (McAdam ellipse)	SDCM1
Exchangeable control gear	Yes
Beam angle adjustable	No
With presence indicator	No