Klemko Techniek B.V.
Phone: +31 (0)880023300
E-mail: info@klemko.nl



## 864510 - LA-IOB-PIR-CCT8-13

Package type: CT á 1 pce



## **PRODUCT SPECIFICATIONS:**

White Colour of light Suitable for suspended mounting No Suitable for ceiling mounting Yes Suitable for wall mounting Yes Suitable for built-in mounting Yes Suitable for surface mounting Yes

Lamp type LED not exchangeable

With light source Yes

Type of control gear LED operating device current-controlled

With control gear Yes Suitable for emergency lighting No Nominal voltage (V) 220 - 240 2700 - 4000 Colour temperature (K) Housing material Plastic Housing colour White Suitable for light line configuration No

Material cover Plastic, opal Light sharing Symmetric

Beam angle Extreme wide beam >80°

Light outlet Direct Length (mm) 240 Width (mm) 240 20 Height/depth (mm) Outer diameter (mm) 240 Built-in height/depth (mm) 20 With movement sensor Yes With light sensor Yes Protection class Covering of the luminaire with thermally Yes

insulating material possible

Max. system power (W) 13 Voltage type AC Colour rendering index CRI 80-89 Dimming 0-10 V No Dimming 1-10 V No Dimming DALI No Dimming DMX Nο Dimming DSI No Dimming potentiometer (integrated) No Dimming manufacturer's proprietary Nο system

Dimming mains voltage modulation No Dimming phase cut-off No Dimming phase cut-on No



Dimming programmable Yes Dimming RF Nο Dimming Touch and Dim No Dimming Zigbee No Dimming with push-button No Operation by Bluetooth No

Light distributor Diffuser lens/optic/panel

Colour consistency (McAdam ellipse) SDCM6 Degree of protection (NEMA) 2 Suitable for lamp power (W) 8 - 13 Type of wiring **Ending** 2 Number of poles Connection type Cable Exchangeable control gear No Dimming DALI-2 No Lumen maintenance at median useful life 96

of 50,000 h at 25 °C ambient (tq) (%)

Colour of light adjustable **Positions** Beam angle adjustable No Compatible with Apple HomeKit No Compatible with Google Assistant No

Compatible with Amazon Alexa No IFTTT support available No Energy efficiency class of the light source Ε

according to EU regulation 2019/2015

Compatible with Casambi No

Passive infrared

Dimmable No

(lm/W) 97.5 - 101 (lm) 720 - 1286

With presence indicator Yes

IP20

Degree of protection (IP), front side IP20

None None

Suitable for clamp-mounting Yes With mounting material Yes With switch No