

Klemko Techniek B.V.  
Phone: +31 (0)880023300  
E-mail: [info@klemko.nl](mailto:info@klemko.nl)

# klemko®

## 866090 - LA-PI-ALU42WH-B

Led armatuur plafond inbouw

Package type: CT á 1 pce

/productimages/866090.jpg



# PRODUCT SPECIFICATIONS:

Spot	
Mounting method	Built-in
Colour temperature (K)	6000 - 6000
Suitable for lamp power (W)	2.1 - 2.1
Max. system power (W)	2.1
Nominal current (mA)	0 - 700
Nominal voltage (V)	3 - 3
Suitable for ceiling mounting	Yes
Suitable for clamp-mounting	Yes
Adjustability	not adjustable
Lamp type	LED not exchangeable
With light source	Yes
Electrical connection with connector system	Yes
Degree of protection (IP)	IP44
Type of control gear	LED operating device current-controlled
With control gear	No
Housing material	Aluminium
Housing colour	Aluminium
Rated luminous flux according to IEC 62722-2-1 (lm)	150
Light sharing	Symmetric
Beam angle	Wide beam 41-80°
Height/depth (mm)	52
Outer diameter (mm)	42
Built-in depth (mm)	50
Voltage type	DC
Colour of light	White
Colour rendering index CRI	80-89
Suitable for built-in mounting	Yes
Optics	Lens
Material cover	Plastic, opal
Light distributor	Diffuser lens/optic/panel
Light outlet	Direct
Built-in diameter (mm)	37 - 37
Number of poles	2
Emergency power supply integrated	No
Colour consistency (McAdam ellipse)	SDCM2
With mounting bracket	No
Energy efficiency class of the light source according to EU regulation 2019/2015	G