

Klemko Techniek B.V.
Phone: +31 (0)880023300
E-mail: info@klemko.nl

klemko®

867650 - MIL11ALU-WW-0,5W

MIL11 industriële led spots

Package type: BG á 1 pce

/productimages/867650.jpg



PRODUCT SPECIFICATIONS:

Spot	
Mounting method	Built-in
Colour temperature (K)	3000 - 3000
Luminaire efficacy (lm/W)	60
Suitable for lamp power (W)	0.5 - 0.5
Max. system power (W)	0.5
Nominal voltage (V)	12 - 12
Suitable for ceiling mounting	Yes
Suitable for clamp-mounting	Yes
Adjustability	not adjustable
Lamp type	LED not exchangeable
Electrical connection with connector system	No
Degree of protection (IP)	IP67
Type of control gear	LED operating device voltage-controlled
With control gear	No
Housing material	Aluminium
Housing colour	Silver
Rated luminous flux according to IEC 62722-2-1 (lm)	30
Light sharing	Symmetric
Length (mm)	22
Width (mm)	15
Beam angle (°)	120
Height/depth (mm)	30
Outer diameter (mm)	15
Built-in depth (mm)	30
Voltage type	DC
Colour of light	White
Colour rendering index CRI	90-100
Suitable for built-in mounting	Yes
(cm)	100
Light distributor	Other
Light outlet	Direct
Built-in width (mm)	11
Built-in diameter (mm)	11 - 11
Number of poles	2
Emergency power supply integrated	No
Suitable for wall mounting	Yes
Exchangeable control gear	Yes
With mounting bracket	No
Energy efficiency class of the light source according to EU regulation 2019/2015	Not required