

Klemko Techniek B.V.
Tel.: +31 (0)880023300
E-mail: info@klemko.nl

klemko®

868218 - LM-ITSP18W-30EWW

Lumiko modulair i-trackspots

Package type: CT á 1 pce

/productimages/868218.jpg



PRODUCT SPECIFICATIONS:

Dimmable	No
Colour temperature (K)	2700 - 2700
Colour of light adjustable	No
Dimming phase cut-off	No
Luminous flux (lm)	1950 - 1950
Rated luminous flux according to IEC 62722-2-1 (lm)	1950
(lm/W)	0 - 108
Nominal voltage (V)	230 - 230
Voltage type	AC
Max. system power (W)	18
Energy efficiency class of the light source according to EU regulation 2019/2015	E
Beam angle	Medium beam 21-40°
Beam angle (°)	30
Length (mm)	86
Width (mm)	86
Height/depth (mm)	181
(mm)	68
Outer diameter (mm)	86
Housing colour	White
Degree of protection (IP), front side	IP20
IP20	
Degree of protection (IP)	IP20
Suitable for ceiling mounting	Yes
Suitable for suspended mounting	Yes
Suitable for wall mounting	Yes
Luminous flux adjustable	No
Suitable for lamp power (W)	18 - 18
Suitable for traverse mounting	No
Suitable for pedestal/floor mounting	Yes
Suitable for light-track mounting	Yes
Suitable for clamp-mounting	No
Adjustability	Rotating and swivelling
With movement sensor	No
With light sensor	No
Lamp type	LED not exchangeable
With light source	Yes
Electrical connection with connector system	Yes
Type of control gear	LED operating device current-controlled
With control gear	Yes
Colour of light	White
Housing material	Aluminium
Reflector	None

Light sharing	Symmetric
Colour rendering index CRI	90-100
Suitable for built-in mounting	No
Optics	Lens
Suitable for low voltage cable system	No
Yes	
Surface protection	Powder coating
Surface brushed	No
Dimming 1-10 V	No
Dimming DALI	No
Dimming DSI	No
Dimming potentiometer (integrated)	No
Dimming LineSwitch	No
Dimming mains voltage modulation	No
Dimming phase cut-on	No
Dimming programmable	No
Dimming Sine Wave Reduction	No
Light distributor	Focal lens
Light outlet	Direct
Number of poles	3
Connection type	Busbar adapter
With mounting bracket	No
Dimming manufacturer's proprietary system	No
Dimming 0-10 V	No
Dimming with push-button	No
Dimming Touch and Dim	No
Dimming DMX	No
Dimming DALI-2	No
Dimming Zigbee	No
Dimming RF	No
(lm)	0 - 1950