

Klemko Techniek B.V.
Phone: +31 (0)880023300
E-mail: info@klemko.nl

klemko®

870880 - IB-RAD-UNI

Aanwezigheidsdetector Inbouw


</productimages/870880.jpg>

Package type: CT á 1 pce



PRODUCT SPECIFICATIONS:

Mounting method	Flush mounted (plaster)
Ceiling	
Degree of protection (IP)	IP20
Response value luminosity (lx)	5 - 1000
HVAC-control	Yes
Optimum mounting height (m)	2.5
Model	Movement sensor
Constant light control	No
No	
Remote operation	No
With remote control	No
(mm)	90
Width (mm)	51
Height (mm)	31.5
Max. mounting height (m)	5
Max. reach sideways (m)	10
10	
Diameter reach on floor (m)	10
(W)	1000
(VA)	200
Number of switching zones	1
High frequency	
Integrated	
Response value sensitivity adjustable	Yes
Response value luminosity adjustable	Yes
Colour	White
RAL-number (similar)	9010
Material	Plastic
Material quality	Thermoplastic
Surface protection	Lacquered
Surface finishing	Matt
Voltage type	AC
Min. switch-on time (s)	5
Max. duty cycle (min)	30
Detection angle horizontal (°)	1 - 360
Nominal voltage (V)	220 - 240
Max. switching power (W)	1000
Max. presence range (m²)	50
Scan angle (°)	360
Connection type	Screw terminal
Frequency (Hz)	50 - 60
Suitable for ceiling mounting	Yes
Suitable for wireless transmission	No
Forced switch off	Yes



With connection cable	No
Yes	
1 make contact (NO)	
Yes	
(m ²)	80
Dim function with dimmer basic element	No
Networkable	No
Compatible with Casambi	No
Compatible with Google Assistant	No
Compatible with Amazon Alexa	No
No	
No	
Transparent	No
IFTTT support available	No