

Klemko Techniek B.V.
Phone: +31 (0)880023300
E-mail: info@klemko.nl

klemko®

871512 - AWD-230-10-shop

Aanwezigheidsdetector Plafond Inbouw

870550.jpg

Package type: CT á 1 pce

PRODUCT SPECIFICATIONS:

Mounting method	Flush mounted (plaster)
Ceiling	
Degree of protection (IP)	IP41
Response value luminosity (lx)	5 - 10000
HVAC-control	No
Optimum mounting height (m)	2.5
Model	Movement sensor
Constant light control	Yes
Remote operation	No
(mm)	70
Built-in size (mm)	45
Max. mounting height (m)	12
Max. reach sideways (m)	15
Max. reach frontally (m)	15.75
30	
Diameter reach on floor (m)	15
Control current (mA)	10
(VA)	2300
Passive infrared	
Response value sensitivity adjustable	No
Response value luminosity adjustable	Yes
Colour	White
RAL-number (similar)	9010
Material	Plastic
Material quality	Thermoplastic
Surface protection	Lacquered
Surface finishing	Matt
Min. switch-on time (s)	14
Max. duty cycle (min)	840
Detection angle horizontal (°)	1 - 360
Nominal voltage (V)	220 - 240
(W)	3
Frequency (Hz)	50 - 60
Suitable for wall mounting	No
Forced switch off	No
Yes	
No	
(m²)	39.2
(m²)	235.5
Yes	