

Klemko Techniek B.V.
Phone: +31 (0)880023300
E-mail: info@klemko.nl

klemko®

871540 - AWD-S-24V10

Aanwezigheidsdetector plafond Inbouw

Package type: CT á 1 pce

/productimages/871540.jpg



PRODUCT SPECIFICATIONS:

Mounting method	Flush mounted (plaster)
Ceiling	
Degree of protection (IP)	IP41
Response value luminosity (lx)	5 - 10000
HVAC-control	No
Optimum mounting height (m)	2.5
Model	Movement sensor
Constant light control	No
Remote operation	No
(mm)	70
Built-in size (mm)	45
Max. mounting height (m)	12
Max. reach sideways (m)	15
Max. reach frontally (m)	15.7
Diameter reach on floor (m)	8
Passive infrared	
Response value sensitivity adjustable	No
Response value luminosity adjustable	Yes
Colour	White
RAL-number (similar)	9010
Material	Plastic
Material quality	Thermoplastic
Surface protection	Lacquered
Surface finishing	Matt
Voltage type	DC
Detection angle horizontal (°)	1 - 360
Nominal voltage (V)	220 - 240
Max. switching power (W)	0.72
Frequency (Hz)	50 - 60
Suitable for wall mounting	No
Forced switch off	No
Yes	
No	
(m ²)	39.2
(m ²)	64.8
No	