Klemko Techniek B.V.
Phone: +31 (0)880023300
E-mail: info@klemko.nl



## 876620 - LED-IB-SM-NW

/productimages/876620.jpg

Led spots, inbouw

Package type: CT á 1 pce





## **PRODUCT SPECIFICATIONS:**

C	n	^	+
J	μ	v	L

Mounting method Built-in Dimmable Yes

4000 - 4000 Colour temperature (K)

Colour of light adjustable No Rated luminous flux according to IEC 215

62722-2-1 (lm)

0 - 102 (lm/W) 0 - 700 Nominal current (mA) Nominal voltage (V) 3 - 3 DC Voltage type Max. system power (W) 2.1 Energy efficiency class of the light source

according to EU regulation 2019/2015

Beam angle Extreme wide beam >80°

Beam angle (°) 90 Built-in height (mm) 14 - 14 Length (mm) 48 Width (mm) 48 Height/depth (mm) 19 Outer diameter (mm) Built-in width (mm) 39 - 40 39 - 40 Built-in diameter (mm) Housing colour Aluminium IP20

Degree of protection (IP), front side

IP20

Degree of protection (IP) IP20 Suitable for suspended mounting No Suitable for wall mounting No

Luminous flux adjustable Continuously variable

Suitable for lamp power (W) 2.1 - 2.1 Suitable for traverse mounting Nο Suitable for pedestal/floor mounting No Suitable for light-track mounting No Suitable for clamp-mounting Yes

Adjustability not adjustable

With movement sensor No With light sensor No

Lamp type LED not exchangeable

With light source Yes Electrical connection with connector Yes

system

Type of control gear LED operating device current-controlled

With control gear No Colour of light White



Housing material Aluminium Reflector High-gloss Light sharing Symmetric 80-89 Colour rendering index CRI Suitable for surface mounting Yes Suitable for built-in mounting Yes (cm) 100 Dimming potentiometer (integrated) No Light distributor Focal lens Reflector colour Silver Light outlet Direct Number of poles 2 Connection type Plug Exchangeable control gear Yes Beam angle adjustable No With presence indicator No None Dimming manufacturer's proprietary No system IFTTT support available No Dimming Touch and Dim No (lm) 0 - 215