Klemko Techniek B.V.
Phone: +31 (0)880023300
E-mail: info@klemko.nl



## 876620 - LED-IB-SM-NW

/productimages/876620.jpg

Led spots, inbouw

Package type: CT á 1 pce





## **PRODUCT SPECIFICATIONS:**

S	D	o	t

Mounting method Built-in Dimmable Yes

Colour temperature (K) 4000 - 4000

Colour of light adjustable No
Luminous flux (lm) 0 - 215
Rated luminous flux according to IEC 215

62722-2-1 (lm)

(lm/W)0 - 102Nominal current (mA)0 - 700Nominal voltage (V)3 - 3Voltage typeDCMax. system power (W)2.1Energy efficiency class of the light source according to EU regulation 2019/2015E

Beam angle Extreme wide beam >80°

Beam angle (°) 90 Built-in height (mm) 14 - 14 Length (mm) 48 Width (mm) 48 Height/depth (mm) 19 Outer diameter (mm) 48 39 - 40 Built-in width (mm) Built-in diameter (mm) 37 - 40 Housing colour Aluminium IP20 Degree of protection (IP), front side

IP20

Degree of protection (IP) IP20
Suitable for ceiling mounting Yes
Suitable for suspended mounting No
Suitable for wall mounting No

Luminous flux adjustable Continuously variable

Suitable for lamp power (W)

Suitable for traverse mounting

No

Suitable for pedestal/floor mounting

No

Suitable for light-track mounting

No

Suitable for clamp-mounting

Yes

Adjustability not adjustable

With movement sensor No
With light sensor No

Lamp type LED not exchangeable

With light source Yes
Electrical connection with connector Yes

system

Type of control gear LED operating device current-controlled



With control gear No Colour of light White Housing material Aluminium Reflector High-gloss Light sharing Symmetric Colour rendering index CRI 80-89 Suitable for surface mounting Yes Suitable for built-in mounting Yes 100 Dimming potentiometer (integrated) No Light distributor Focal lens Reflector colour Silver Light outlet Direct 2 Number of poles Connection type Plug Exchangeable control gear Yes Beam angle adjustable No Lamp power (W) 2.1 With presence indicator No None Dimming manufacturer's proprietary No system IFTTT support available No Dimming Touch and Dim No 0 - 215 (lm)