

Klemko Techniek B.V.  
Phone: +31 (0)880023300  
E-mail: info@klemko.nl

# klemko®

## 876638 - LED-IB-SP-CW-AL

LED meubelspots

/productimages/876638.jpg

Package type: CT á 1 pce



# PRODUCT SPECIFICATIONS:

|  |   |
|--|---|
| Spot   |   |
| Colour temperature (K)   | 6000 - 6000                             |
| Luminaire efficacy (lm/W)  | 102                                     |
| Suitable for lamp power (W)  | 2.1 - 2.1                               |
| Max. system power (W)  | 2.1                                     |
| Nominal current (mA)   | 0 - 700                                 |
| Nominal voltage (V)  | 3 - 3                                   |
| Suitable for ceiling mounting  | Yes                                     |
| Adjustability  | not adjustable                          |
| Lamp type  | LED not exchangeable                    |
| With light source  | Yes                                     |
| Electrical connection with connector system                                      | Yes                                     |
| Degree of protection (IP)  | IP20                                    |
| Type of control gear   | LED operating device current-controlled |
| With control gear  | No                                      |
| Housing material   | Aluminium                               |
| Housing colour   | Aluminium                               |
| Rated luminous flux according to IEC 62722-2-1 (lm)                              | 215                                     |
| Light sharing  | Symmetric                               |
| Beam angle   | Extreme wide beam >80°                  |
| Beam angle (°)   | 90                                      |
| Height/depth (mm)  | 16                                      |
| Outer diameter (mm)  | 64                                      |
| Built-in depth (mm)  | 15                                      |
| Voltage type   | DC                                      |
| Colour of light  | White                                   |
| Colour rendering index CRI   | 80-89                                   |
| Suitable for surface mounting  | Yes                                     |
| Suitable for built-in mounting (cm)  | Yes<br>100                              |
| Light distributor  | Focal lens                              |
| Light outlet   | Direct                                  |
| Built-in height/depth (mm)   | 13                                      |
| Built-in diameter (mm)   | 58 - 58                                 |
| Number of poles  | 2                                       |
| Emergency power supply integrated  | No                                      |
| With mounting bracket  | No                                      |
| Energy efficiency class of the light source according to EU regulation 2019/2015 | E                                       |