

Klemko Techniek B.V.
Phone: +31 (0)880023300
E-mail: info@klemko.nl

klemko®

/productimages/876742.jpg

Led spots. inbouw

Package type: CT á 1 pce



PRODUCT SPECIFICATIONS:

Spot	
Mounting method	Built-in
Colour temperature (K)	3000 - 3000
Luminaire efficacy (lm/W)	102
Suitable for lamp power (W)	2.1 - 2.1
Max. system power (W)	2.1
Nominal current (mA)	0 - 700
Nominal voltage (V)	3 - 3
Adjustability	Rotating and swivelling
Lamp type	LED not exchangeable
With light source	Yes
Electrical connection with connector system	Yes
Degree of protection (IP)	IP44
Type of control gear	LED operating device current-controlled
With control gear	No
Housing material	Aluminium
Housing colour	Black
Moulded-on	
Rated luminous flux according to IEC 62722-2-1 (lm)	215
Light sharing	Symmetric
Beam angle	Medium beam 21-40°
Beam angle (°)	35
Height/depth (mm)	27
Outer diameter (mm)	50
Built-in depth (mm)	27
Voltage type	DC
Colour of light	White
Colour rendering index CRI	80-89
Suitable for surface mounting	No
Suitable for built-in mounting	Yes
Optics	Lens
(cm)	100
Light distributor	Focal lens
Light outlet	Direct
Built-in height/depth (mm)	27
Built-in diameter (mm)	44 - 44
Number of poles	2
Connection type	Push-in clamp
Emergency power supply integrated	No
Colour consistency (McAdam ellipse)	SDCM1

Exchangeable control gear	Yes
Luminous flux adjustable	Continuously variable
Beam angle adjustable	No
With mounting bracket	No
Energy efficiency class of the light source according to EU regulation 2019/2015	E