

876756 - SPOT-62RB-NW-WH

Led spots, inbouw

Package type: CT á 1 pce

863720.jpg

klemko

PRODUCT SPECIFICATIONS:

Spot	
Mounting method	Built-in
Colour temperature (K)	4000 - 4000
Luminaire efficacy (lm/W)	102
Suitable for lamp power (W)	2.1 - 2.1
Max. system power (W)	2.1
Nominal current (mA)	0 - 700
Nominal voltage (V)	3 - 3
Suitable for ceiling mounting	Yes
Adjustability	Rotating and swivelling
Lamp type	LED not exchangeable
With light source	Yes
Electrical connection with connector system	Yes
Degree of protection (IP)	IP44
Type of control gear	LED operating device current-controlled
With control gear	No
Housing material	Aluminium
Housing colour	White
Rated luminous flux according to IEC 62722-2-1 (lm)	215
Light sharing	Symmetric
Beam angle	Medium beam 21-40°
Beam angle (°)	35
Height/depth (mm)	27
Outer diameter (mm)	62
Built-in depth (mm)	27
Voltage type	DC
Colour of light	White
Suitable for surface mounting	No
Suitable for built-in mounting	Yes
Optics	Lens
(cm)	100
Light distributor	Focal lens
Light outlet	Direct
Built-in height/depth (mm)	27
Built-in diameter (mm)	50 - 50
Number of poles	2
Emergency power supply integrated	No
Luminous flux adjustable	Continuously variable
Beam angle adjustable	No
Energy efficiency class of the light source according to EU regulation 2019/2015	Ε