

Klemko Techniek B.V.
Phone: +31 (0)880023300
E-mail: info@klemko.nl

klemko®

891042-AP - D-PAF-200-LED-5x

891038.jpg

Package type: CT á 5 pce

PRODUCT SPECIFICATIONS:

Assembly arrangement	Basic element with complete housing
Method of operation	Turn/push button
Protocol	Phase cut-off
Type of load	Universal and LED Retrofit
Nominal voltage (V)	220 - 240
Frequency (Hz)	50 - 50
Nominal power resistive load (W)	1 - 200
Dimming phase cut-off	Yes
(st)	15
(st)	15
Mounting method	Flush mounted (plaster)
Type of fastening	Mounting with claw and screw
Suitable for degree of protection (IP)	IP20
Device height (mm)	71
Device width (mm)	71
Axis length (mm)	10
Material	Metal
Surface finishing	Glossy
Colour	Aluminium
Applicable with button	Yes
Light value memory	Yes
Applicable with transmission button	No
Applicable with infrared button	No
App control via Bluetooth	No
Dimming phase cut-on	No
Nominal power inductive load (VA)	1 - 200
Nominal power capacitive load (VA)	1 - 200
Connection type	Push-in clamp
Core cross section (mm ²)	0.75 - 2.5
(mm)	71
Width (mm)	71
Depth (mm)	33
Min. depth of built-in installation box (mm)	35
Max. switching power LED (W)	200
Compatible with Apple HomeKit	No
Compatible with Google Assistant	No
Min. brightness controllable	Yes
Substation input	Yes
Transparent	No
Serial dimmer	No